

>



Model Number: 20120606

20120606, Pressure Washer QD to Rust Bleeder, to Filtered Insulated Carpet Cleaners QD, Female Socket as first Piece

Manufacturer: Clean Storm

Clean Storm 20120606: Pressure Washer QD to Rust Bleeder to Filtered Insulated Carpet Cleaners QD

Description:

Pressure washing water heaters/burners are made of steel so small particles of rust can clog the finer jets used for tile, carpet, and upholstery cleaning.

Solution to this is to connect 20120606 into pressure washers QD that has male 3/8" QD connections(horizontal) into tee fitting to bleed out rust from burner (faces downward/ vertical) > to high pressure filter (horizontal) and insulated carpet and tile cleaning female quick disconnect. Now you will have an easy to to bleed out the rust while filtering it out at the same time. The insulated carpet cleaners QD makes it easy to remove you carpet cleaning hoses. When you start the job run the first 2 minutes of water out the ball valve to clear out as much rust as possible. Installed filter and carpet cleaning QD are slightly elevated. Tee fitting is vertical with the hose downward and carpet QD and filter on top. As the water leaves the burner the rust will hit the "T" and lets the rust fall into the 60" long hose. Only the cleaner water will flow up hill to the high pressure filter and out the QD.

Quick connection let you easily toggle between using tile and carpet cleaning hose or remove and use your pressure washing hoses.

Please note that the ball valve is only rated for 600 psi and depending on the heat and pressure you use, you might wear it out. We have installed the ball valve at the end of the 60" long hose so it will not be roasted by the heater.

We want you to point the back hose vertical (downward) so any rust that comes out of the heater will flow to the hose and valve while the cleaner water will travel upwards through the high pressure filter and insulated QD.

Please note for shipping reasons we will not completely tighten all fittings so please tape and retighten as need to ensure it will not leak for you.

Video

Includes one each of the following:

Truckmount 3/8" Brass Ball Valve

>

Pressure Washer Coupler 3/8" Mip X 3/8" Female Coupler QD

1/4in Safety Female Quick Disconnect QD

line filter Landa Hotsy Shark Legend 1/4 inch pipe 5000 psi High pressure in

J.E. Adams: 90 Degree 3/8" Street Elbow---Used with JE Adams
booms Item #6050 and Item #6083

>

Nipple Brass 1/4" Male Pipe X 3/8" Mip Pipe

Brass Tee 3/8" Fip X 3/8" Fip X 3/8" Fip Brass

Clean Storm Truckmount Repair Hose 3/8" Mip X 3/8" Mip X 60" L
4000psi Double Wire 3/8" ID

Optional:

>

The above filter assembly is included with this starter package
.Steambrite 22 Hp TruckMount Predator Engine Tuthill 3006 (36) Blower
Stainless Carpet Cleaning Machine Only w/ Freshwater Tank TM2236

Upgrade ball valve to high pressure
Clean Storm 3/8" Fip Full Port High Pressure Ball Valve Steel 7250 psi

Male Nipple Plug 3/8 in Stainless Steel Quick Coupler 87071520 QD
Some customer will need the female socket replaced with male plug as the
first piece based on the brand of pressure washer you are using.

Additional Information
Northern Tool pressure washers need Female
BE Pressure need Male
Hydrotek do not include couplers so you typically purchase an extra male plug X male
pipe and then purchase the standard female socket rust bleeder. Then also purchase
an additional 3/8 female socket X 3/8" female pipe coupler for your hose. Then you
can toggle between pressure washing and carpet and tile cleaning.

E20190822JMG

Availability: This product was added to our catalog on Thursday 06 June, 2013