



Model Number: 750137

Powerhorse 750137 Portable Generator 2500 Surge Watts 2000 Rated Watts EPA Compliant 212cc

Manufacturer: Powerhorse

Powerhorse 750137 Portable Generator 2500 Surge Watts, 2000 Rated Watts, EPA Compliant 212cc

Product Summary

This Powerhorse Portable Generator prepares you for emergencies and a variety of outdoor projects. Equipped with 100% copper-wound generator head for continuous operation without overheating. Less than 5% THD safely operates sensitive electronics.

Not for sale in California.

HIGH ALTITUDE OPERATION

CAUTION: Operating at an altitude of greater than 2000 feet (610 meters) may affect your engine's performance, fuel consumption, and emissions. To remain emissions compliant and improve engine performance at higher altitudes, a high-altitude kit is required. A high altitude kit includes a carburetor jet resized to help correct air / fuel mixture at altitude. To order a high altitude kit, or if you have additional questions, contact us at 1-866-443-2576. Please note, engines with the high-altitude kit installed operated at lower altitudes could cause severe engine damage and affect emissions compliance. When modified, a tag or decal should be added to the product stating that a high-altitude kit was installed and to remind you to re-service the carburetor (re-jet) when operating in lower altitude environments.

What's Included

- (1) Portable generator
- (1) Wheel kit with flat-free tires

Product Manual

Features + Benefits

- 212cc engine
- Four 120V, 20A outlets and one 12V DC outlet
- 100% copper-wound generator head allows continuous operation without overheating
- Less than 5% THD safely operates sensitive electronics
- Automatic voltage regulator with voltmeter
- Low oil shutdown
- 11-hour run time @ 1/2 load
- 3.9-gallon fuel capacity
- Includes wheel kit with flat-free tires

Key Specs

>

Item#
750137

Brand
Powerhorse

Manufacturer's Warranty
2yr consumer/90 day commercial

Ship Weight
102.0 lbs

Surge Watts
2,500

Rated Watts
2,000

Start Type
Recoil

Engine
DH212

Engine Displacement (cc)
212

Run Time
11 hrs. at 1/2 load

Receptacles (qty.)
(4)120V, 20A outlet, (1) 12V DC outlet

Fuel Type
Gasoline

>

Fuel Capacity (gal.)
3.9

Low Oil Shutdown
Yes

Battery Included
No

Battery Required
No

CARB Compliant
No

Dimensions L x W x H (in.)
25 2/5 x 18 3/4 x 19 3/4

Availability: This product was added to our catalog on Friday 14 September, 2018