

>



Model Number: 8000-533-236

Shurflo 8000-533-236, 60psi 115volt, 1.4GPM With Pressure Switch, GTIN 752324006595

Manufacturer: Shurflo

Shurflo- Diaphragm Pump 3 Chamber, 1.4 GPM Open Flow, 115VAC Intermittant Duty, 60 PSI Demand Switch (adjustable 40-60 PSI), Viton Valves, Santoprene Diaphragm, Polypropylene Housing, 3/8" NPT Female Ports, UL/CSA Recognized, Typical Application: Soil Extraction, Carpet Cleaning

ShurFlo 115VAC 1.4 GPM Transfer Diaphragm Pump

ShurFlo 8000-533-236 Industrial Transfer Diaphragm Pump

115 Volt AC, 1.4 GPM open flow, 60 PSI Demand switch, Viton valves, Santoprene diaphragm. 3/8" NPT Poly (Female) Ports

- PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump
- CAM: 3.0 Degree
- CHECK VALVE: (2-Way Op.) Prevents Reverse Flow & 6 Ft. Head Forward Flow
- MOTOR: Permanent Magnet, P/N 11-150-00, Thermally Protected
- VOLTAGE: 115 VAC Nominal
- PRESSURE SWITCH: Adjustable Shut-Off (Range 40-60 PSI), Factory Set @ 60 PSI, Turn On 45 PSI +/- 5 PSI
- LIQUID TEMPERATURE: 170 Degrees Fahrenheit (77 Degrees Centigrade) Max.
- PRIME: Self-Priming Up To 8 Ft. Vertical,
- Max. Inlet Pressure 30 PSI (2.1 Bar)
- PORTS: 3/8"-18 NPT Female
- MATERIAL OF CONSTRUCTION:
 - PLASTICS- Polypropylene
 - VALVES- Viton
 - DIAPHRAGM- Santoprene
 - FASTENERS- Zinc Plated Steel
- NET WEIGHT: 3.8 Lbs (1.72 Kg)
- DUTY CYCLE: Intermittent
- TYPICAL APPLICATIONS: Soil Extraction
- GTIN 752324006595

International shipping?

You can ship either one or two of these pumps for the same \$135 by the US Post Master to almost every country in the world.

- Model: 8000-533-236
- Shipping Weight: 4lbs
- Manufactured by: SHURflo

>

Kleenrite \$147.73

-->

Availability: This product was added to our catalog on Thursday 03 November, 2011