

>



Model Number: 09IHSS

Innovative Surface Solutions 09IHSS Lithium Silicate Hardener concrete travertine limestone terrazzo Gallon

Manufacturer: Innovative Surface Solutions

Innovative Surface Solutions 09IHSS Lithium Silicate Hardener concrete travertine limestone terrazzo
1 Gallon

This product is a lithium silicate sealer, hardener and densifier for concrete, terrazzo, travertine, and limestone surfaces.

This penetrating product reacts with each surface to produce insoluble calcium silicate hydrate within the pores of the concrete, terrazzo, travertine, and limestone. Surfaces treated with this product resist damage from water and surface abrasion.

MATERIAL SAFETY DATA SHEET

SECTION

I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: LITHIUM SILICATE HARDENER RTU ID NUMBER: ISS-2575
PRODUCT USE/CLASS: CONCRETE DENSIFIER
MANUFACTURED FOR: Innovative Surface Solutions 1229 Simpson Way,
Escondido CA, 92029 TELEPHONE: 800-280-0333
PREPARED BY: REGULATORY DEPT. EMERGENCY TELEPHONE: 800-633-8253
PREPARE DATE: 07/10/2012

SECTION

II - COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME
CAS NUMBER
WT.PERCENT
IS LESS THAN
TLV-TWA
TLV-STEL
PEL-TWA
SKIN
DESIGNATION
Silicic acid, lithium salt; 12627-14-4 < 15.0% N/E N/E N/E NO
lithium silicate
(See Section 11 for abbreviation legend)

>

SECTION

III - PHYSICAL DATA

BOILING RANGE: 212 - 237 F VAPOR DENSITY : Is heavier than air ODOR:
CHARACTERISTIC SPECIFIC GRAVITY: 1.0305
APPEARANCE: CLEAR LIQUID PH: 9.8 to 10.2 EVAPORATION RATE: SLOWER
THAT ETHE SOLUBILITY IN H2O : COMPLETE
(See Section XI for abbreviation legend)

SECTION

IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A (WATER-BASED LIQUID) LOWER EXPLOSIVE LIMIT: N.A.
UPPER EXPLOSIVE LIMIT: N.A.
EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG
UNUSUAL FIRE AND EXPLOSION HAZARDS: THIS PRODUCT
NONCOMBUSTIBLE. IT MAY DECOMPOSE RELEASING OXYGEN,
INTENSIFYING THE FIRE. A STRONG OXIDIZER, IT MAY INITIATE COMBUSTION
OF ORGANIC MATERIALS OR EXPLOSION OF FLAMMABLE LIQUIDS.
SPECIAL FIREFIGHTING PROCEDURES: COOL CONTAINERS IN VICINITY TO
PREVENT OVERHEATING. FIREFIGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS AND PROTECTIVE CLOTHING.

SECTION

V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE : OVER EXPOSURE IS HIGHLY UNLIKELY.
NATURESOL IS DISPENSED THROUGH A CONTROLLED DISPENSING STATION.
ALL END USER CONTACT IS IN A DILUTED FORM.
EFFECTS OF OVEREXPOSURE - EYE CONTACT: EYE CONTACT WILL CAUSE
IRRITATION.
EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED
CONTACT MAY CAUSE IRRITATION TO SENSITIVE SKIN.
EFFECTS OF OVEREXPOSURE - INHALATION: EXCESSIVE INHALATION MAY
CAUSE NAUSEA, DIZZINESS.
EFFECTS OF OVEREXPOSURE - INGESTION: CORROSIVE. LARGE
QUANTITIES COULD CAUSE PAIN, NAUSEA.
EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: NO INFORMATION.
FIRST AID - EYE CONTACT: FLUSH WITH WATER 15-30 MINUTES, LIFTING
EYELIDS. GET MEDICAL ATTENTION.
FIRST AID - SKIN CONTACT: FLUSH WITH WATER 15 MINUTES. REMOVE
CONTAMINATED CLOTHING. LAUNDER BEFORE REUSE. GET MEDICAL
ATTENTION IF IRRITATION PERSISTS.
FIRST AID - INHALATION: REMOVE TO FRESH AIR. IF IRRITATION PERSISTS
GET MEDICAL ATTENTION.
FIRST AID - INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES

>

OF WATER OR MILK. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION. GET MEDICAL ATTENTION.

PRIMARY ROUTE(S) OF ENTRY: INGESTION EYE CONTACT

(Continued on Page 2)

Page 2

PRODUCT NAME: LITHIUM SILICATE HARDENER RTU ID NUMBER: ISS-2575

PRODUCT USE/CLASS: CONCRETE DENSIFIER

SECTION

VI - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS: No Information.

CONDITIONS TO AVOID: ACIDS, STRONG OXIDIZING OR REDUCING MATERIALS.

INCOMPATABILITY: ACTIVE METALS. ORGANIC MATERIALS.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is not stable under normal storage conditions.

SECTION

VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WEAR APPROPRIATE PROTECTIVE AND RESPIRATORY EQUIPMENT. PREVENT SPILLS FROM ENTERING SEWERS, OR ANY UNAUTHORIZED WATER SYSTEMS. SPILL MAY BE ABSORBED ONTO APPROPRIATE ABSORBENT MATERIAL.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH APPROPRIATE FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION

VIII - SAFE HANDLING AND USE INFORMATION

VENTILATION: SUFFICIENT VENTILATION, IN VOLUME AND PATTERN, SHOULD BE PROVIDED TO KEEP AIR CONTAMINATION BELOW CURRENT APPLICABLE OSHA PERMISSIBLE EXPOSURE LIMIT OR ACGHI'S TLV LIMIT.

SKIN PROTECTION: RUBBER GLOVES NEEDED.

EYE PROTECTION: SAFETY GLASSES SHOULD BE USED WHEN USING THIS PRODUCT.

OTHER PROTECTIVE EQUIPMENT: PREVENT PROLONGED CONTACT. EYE WASH, SAFETY SHOWER AVAILABLE.

HYGENIC PRACTICES: WASH AFTER EACH USE.

SECTION

IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL

>

DRY AREA KEEP AWAY FROM SPARKS AND OPEN FLAMES.
OTHER PRECAUTIONS: OBEY ALL HAZARD WARNINGS WHEN CONTAINERS
ARE EMPTIED.

SECTION
X - HMIS RATINGS

HMIS RATINGS HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

SECTION
XI - OTHER REGULATIONS

SARA SECTION 313: This product contains the following substances subject to the
reporting requirements of Section 313 of Title III of the Superfund Amendments and
Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT %

No SARA Section 313 components exist in this product.

PREVIOUS MSDS REVISION DATE: N.A

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate.
However, since the conditions of handling and use are beyond our control, we make
no guarantee of results, and assume no liability for damages incurred by use of this
material. It is the responsibility of the user to comply with all Federal, State, and Local
laws and regulations.

<END OF MSDS>

Availability: This product was added to our catalog on Friday 24 May, 2013