

>



Model Number: 20130628

Clean Storm 20130628 Restaurant Carpet Cleaning Machine Bundle Goliath 27gal 8Stage Vacs 1500psi Pressure Washer Recovery

Manufacturer: Clean Storm

Clean Storm 20130628 Restaurant Carpet Cleaning Machine Bundle Goliath 27gal 8Stage Vacs 1500psi Pressure Washer Recovery

This is not your typical carpet cleaning or tile cleaning or upholstery cleaning machine.

More vacuum means it can run longer hoses and dry the carpet and upholstery faster and the ability to clean 20% faster with 14" wide tools.

Set up in one place and clean all surfaces. No need to relocate your equipment from room to room.

More pressure at 1500 psi means you can clean tile 20% faster than other systems that only offer 1200 psi.

More tools for more surfaces inside and out. From the parking lot to touchless bathroom cleaning.

All electric system can stay lock up inside the building for high security.

Having professional cleaning equipment on site can save thousands of dollars a year on cleaning services and make available immediate response to cleaning needs such as wet carpet, vomit cleaning,...

Optional air duct cleaning and vent-a-hood cleaning tools.

## Restaurant Carpet Cleaning Machine Package

Click on each link below to open in new window to learn more about that item

DriStorm Goliath Flood Pumper 26gal 4/2 Stage Vacs Pressure Washer Recovery 120v APO SBM-GO-A SBMGOA 20220803

- Accessories + No Miscellaneous
- Agitation PreScrubbing Equipment + None
- Air Mover Fan + None
- Crevice Tool Option (Floor) + None
- Extended Warranty + No Extended Warranty
- Hoses + No Hoses Included

>

- Hour Meter-Panel Mount (120v) + None
  - Shipping Surcharges + None Commercial Address Forklift / Loading
- Dock On Site No Appointment Provided
- Voltage + 120 Volt - U.S. Current
  - Wand (Carpet Cleaning) + No Carpet Clean Wand Upgrade
  - Wand (Hand Tool) + No Hand Tool Included

BE Pressure P152EC PowerEase 2 Hp 1500 psi Pressure Washer Tile  
Cleaning Pump on Cart 777897154719

- Extended Warranty + No Extended Warranty
- Shipping Surcharges + None Commercial Address Forklift / Loading

Dock On Site No Appointment Provided

Clean Storm 20210819, Pressure Washer to Carpet cleaning  
Connection QD, SBMP-C

Clean Storm Auto Fill Hose 6 ft By 1/2 Inch ID with 90 degree Fitting  
for Hot water Garden Hose 20130305

>

Clean Storm 20121212, Hose Set 115 ft Bundle, Dual 50 ft 2 in 15 ft  
1.5in ID Vacuum 1/4 in 3000 psi Solution Connections QDs

AH54 Clean Storm Ball Valve 1/4in Male X Female Pipe 1000 psi  
Chrome Plated Brass AH57 PMV60804 1692-2484

Clean Storm AH44 Vacuum hose Cuff 2in Thread X 2.0in Slip - 2in  
Standard 8.708-904.0 B016 J11630 530009

Shazaam SBM230 Kryptonium High pH Degreaser - Degrease All  
Surface Types (Purple) 1 Gallon

>

Harvard Chemical 12100101 GelZov Gel D-Limonene Gum and  
grease Spotter 16 oz Gel-Zolv GTIN 711978404867

Westpak 10-0556-Kit 14in Carpet Cleaning Wand Starter Package  
1.5in Pipe 4 Jet 2 Bend Low Profile W/ Splash Guard

HydroForce AS08P, Injection Sprayer Plus High Pressure, with blow  
molded jug, 1639-0775

>

Northstar 32154 5000Psi Pressure Gauge Pressure Washing QD Fits  
all Pressure Washers GTIN 670437122080

PMF U1574S, Easy Grip Tools, 4-1/2in Internal Spray, Brass Valve, 6ft  
Hide A Hose Hand Wand, Esteam 255-085  
- Add-ons + None  
- Quick Disconnect Coupler Needed - None

PMF CV56SBG-GHP Crevice 56In Long Tool Boot/Easy Glide Grout  
and Tile Wand Internal Spray 3000psi Top Mounted HD Valve  
- Quick Disconnect Coupler Needed - None  
- Shipping Surcharges + Signature Required On All Deliveries

Mosmatic 78.292 Tile and Grout Spinner 12 Inch Wand FL-AER 300  
With Vacuum Air Recovery Pick up 4000 psi Sirocco SC-12v

>

Clean Storm AH46 Vacuum Hose Enlarger Cuff Expander 1.5in  
Threaded X 2.0in Slip 19-027 579-012 8.685-673.0

PMF U1590SB Grinder Hard Surface 4-1/2in Wide 500psi Internal  
Spray Specialty Hand Tools Scrubber Detailer Wand  
- Add-ons + None  
- Option 1 + None  
- Quick Disconnect Coupler Needed - None  
- Valve Upgrade + None

Mip Hex Reducing Nipple Brass BR132 1/4in Mip X 3/8in 8.705-227.0  
Kaivac CSS119

Foster FK2B, Bretco 1/4in Male Brass Quick Disconnect, QD Nipple

>

Plug Coupler, QD40 8.756-044.0

Clean Storm 291A Faucet Adapter 15/16ths to Garden Hose  
Connection FGHA AX22 (fits most 13/16ths) 1665-0273 Kaivac

Training DVD Package of 3 Covers the basics a Cleaner needs to  
know SBMdvdpak All Orders Final

Goliath Vacuum System  
Quad Vac Flood pumper with tools to clean every surface!  
The Industries Strongest Electric Water Extraction Machine!  
Tank Size: 20 gallon  
Body Construction: Fiberglass box for durability,  
Vacuum Motors: Four 2 stage vacuums (8 stages total will operate over 200 ft of 2"  
vacuum hose!) Vacuum motors are configured: each pair is in series and then both  
pairs are in parallel for the best of both worlds of high cfm and high inches of lift.  
Automation: 30 GPM STAINLESS STEEL sump pump with water level sensor  
(machines automatically dumps the dirty water as you clean for non stop production)  
Draws only 4 amps.

>

## Factory Installed Clean Storm 30 GPM Stainless Steel Automatic Dump Drain Dirty Water Discharge Pump Out 12499 Mytee C384 12499

### Features:

- Dual ball float/standpipe,
- Clear dome lid on slotted hinged,
- Dual 50 ft. 12-3 power cords,
- Circuit locator,
- 12" rear wheels and swivel casters in the front.
- Front mounted GFI w/ waterproof cover.
- Built in Auto Defoamer with adjustment knob.
- Dual waste water discharge - Garden hose for cleans and 1-1/2" dump hose for floods (your choice)
- Machine will operate on either one or two power cords (see below).
- Made in the USA

### Technical Specification:

- Primary cord (20 amp) runs (2) vac motors in air series with ball float shutoff and sump pump. If a secondary circuit is not available, machine would perform on this cord. Wired with an in-line GFI and cooling fan.
- Secondary circuit (15 amp) runs the (2) other vac motor in air series with a ball float shutoff and check valve.
- 2" vacuum intake.
- Hose mount Stainless steel screen lint catch to protect your auto dump pump.
- Garden hose camlock adapter for carpet and tile cleaning
- 1-1/2" cam lock adapter for flood restoration (seen in photo below)
- (5) Green lighted splash proof rocker switches.
- Blue tank/Grey base
- 170" of Lift (normally dual 2 stage in series would only achieve 155" of lift but these MaxVac vacuum motor are actually doing 170" in series! This is one of the reasons we chose this set up. These are not inflated numbers!)
- 42,500 vacuum units (maximum 170 inches of lift X maximum 250 CFM) make this one of the strongest electric machines on the market
- Gallon of liquid defoamer can be set on top of extractor on jobs where you need to cut some suds. (auto dump systems only dump water and not bubbles)
- Includes hose mount lint filter.



>

Dealer Provided Hydro-Force: Truckmount Carpet Cleaning Lint Filter AC10  
HydroFilter

Factory Installed Valterra PX10: Gate Valve 1.5in Replacement Dump Valve  
H225 Drain Valve

P152EC is the perfect pressure washing pump for home use and professional tile and  
grout cleaning.

Pump is designed to handle hot water up to 140 degrees.

Adjustable pressure regulator.

Built in garden hose filter.

25 ft 4000 psi 3/8" ID pressure hose

Lance with assist handle and 4 quick change nozzles

Build in soap injector only works with large soap injector nozzle attached (low  
pressure spraying). (included)

Amp draw is 10 amps, + 1 amp for each 200 psi you ask it to push the water.

For example 1000 psi is 15 amps and 1500 psi is 17.5 amps

Pressure washer use Weight 100 lbs

Description

>

## FEATURES

Baldor Electric 2 HP Motor

Comet Triplex Pump

2.0 GPM 1500 PSI

Cords, plugs and switch included

UPC 77897104868 (subject to change)

Please note a 20 amp breaker is needed to clean at 1500 psi. If you only have 15 amp outlet, please turn pressure washer down to below 1100 psi.

>

Quad 2 Stage Max Vac Vacuum motors are mounted vertical for longer bearing life.

#### Unit Measurements:

- Handle height is 39". Machine dimensions" 41" H x 24" W x 30" L
- Weight (assembled) = 86 lbs. w/out cords.

#### Goliath Advantages:

1. 27 gallon recovery tank
2. Auto defoamer needle valve
3. 2" vac port will run either 2" or 1-1/2" vacuum hose
4. The highest lift and highest CFM extractor on the market. Nothing comes close. This machine is impressive when it comes to suction. This machine will run longer hose lengths and dry carpet better than any other electric machine that is operating on two power cords.
5. Will operate on one 15 amp power cord, will operate on two 7 amp power cords, will operate on two 15 amp power cords, will operate on two 20 amp power cords. Just turn off features in applications where you have less power available.
6. Optional Stainless steel dump valve is another industry first. You will not be able to brake it or clog it or wear it out.
7. Dual port water pump out discharge. Choose between dumping out a garden hose or out a 1-1/2" vacuum hose, your choice.
8. Switch plate cover will keep your water resistant switch covers in place. Unlike some other brands the clear water protection cover can fall off once the machine gets old or if it gets knocked around.
9. Now available with an optional internal 500 psi PumpTec pump in it to use as a more basic carpet cleaning machine.

#### Owner's Manual

These results were achieved with an open vacuum tank

#### POWERFUL 30GPM AUTO DUMP

Shade/Color is not guaranteed. The current color is Blue.

Auto Defoamer with adjustment knob

>

QUAD TWO-STAGE VACUUM MOTORS IN SERIES/PARALLEL  
AS PER MANUFACTURERS RECOMMENDATION, MOTORS ARE MOUNTED IN A  
WAY THE BALANCES THE VACUUM (lift) AND THE VOLUME (cfm), BY  
MOUNTING THE VACS IN SERIES PAIRS THEN THE PAIRS ARE MOUNTED IN  
PARRALLEL. THIS BALANCES THE LIFT AND CFM, GIVING BETTER  
PERFORMANCE THAN HAVING ALL 4 MOTORS IN SERIES (high lift but nominal  
cfm) OR ALL 4 IN TANDEM (plenty cfm but wimpy vacuum). SO FAR ONLY  
STEAMBRITE MFG GIVES YOU THIS SUPERIOR DELIVERY SYSTEM FOR 4 VAC  
MOTORS.

MACHINE ONLY!! For cost w/accessories, see package options!  
One Year Warranty Included, Optional add 2 or 4 more years to the warranty!

Receive half price shipping if you pick up at SteamBrite San Antonio, TX

To see our vacuum motor testing visit  
<https://www.steam-brite.com/forum/showthread.php?p=3004#post3004>  
Starter packages available to clean:  
Air Ducts, Tile and Grout Cleaning, Water Extraction, Carpet Cleaning (either high  
flow and high pressure),  
Auto Detailing, Mattress, Upholstery, and Drape Cleaning.  
Turn your Goliath into the worlds strongest shop vac with:

Shazaam: Dry Vacuum Option for Goliath Extractor  
Manufacturer: Shazaam

shipping weight is 141#s including pallet; dimensions are: 48 X 40 X 48

OPTIONS:

Shazaam  
Truckmount Kit

>



>

Shazaam: Convert Portable to a Truckmounted Carpet Cleaning Machine and  
Leave outside with Generator, Reel, Power Cord

Clean Storm  
SBHS3000

-Clean Storm Hose Set - 50ft (15 Meters) x 2.0in ID Vacuum & 1/4 in  
3000 psi Solution with QDs installed

Need more hose, add more hose. The Goliath vacuum system can handle  
215 ft with ease!

Optional On Site Permanent Closest Restaurant Installation: Do not confuse this system with central vacuum systems that offer wet cleaning. This system is twice the vacuum power and ten times the water pressure. Use optional 2" ID PVC pipe in the walls for a permanent installation to hide some of the vacuum hose. The vacuum is strong enough to pull the water and air up and over walls or through pipe laid in the foundation. The Goliath vacuum system can be left in a closet to operate and only needs an exhaust fan and two 20 amp 120 volt electric breakers with water sewage drain. The AC10 hose mount filter can either be left in the closet or used in the room that is being cleaned but must be cleaned as needed. If you leave in the closet the operator will not be able to see when it needs to be cleaned and if you leave it up to the operator to relocate you can end up with a worker that cuts corners and fails to set up. Please consider two hose mount vacuum filters. This way you can leave one in the closet and one for the room being cleaned. In a normal installation using the supplied vacuum hose, the hose mount filter is mounted within five feet of the Goliath vacuum system and the operator will have to empty and rinse off after each job (it will be full). Air conditioning and heating system should also be considered in closet to insure longer equipment life. Do not allow to equipment to freeze. Pressure washing pump can also be left as permanent installation. The pump can be removed from the portable dolly and mounted on a shelf (horizontal installation required). You can also consider running pressure hose in wall but this is more challenging because of having to install specialty ball valves and connections at the wall junctions. The use of 'reverse bullnose wall plate' can be used to hang the ball valve handle but please note that some of the water connection will hang out of the wall. We also upgrade the single wire 1/4" hose to double wire 3/8" hose for internal wall use. This type of double wire hose is rated for over 5000 psi and will help ensure the hose will never break or leak in the wall. OR a permanent wall mount hose reel can also be installed in equipment closet. Normally on these reels we install 160 feet of 1/4" non marking hose jacket hose. If you need a longer section of hose you can just add a 50 foot section on the wall. This will give you 210 feet from the equipment closet. To leave

>

the pump as a permanent installation will require another 20 amp 120 volt electrical outlet, hot water garden hose connection and drain. If you need a system to clean more than 210 ft from your equipment closet we have booster vacuum systems for this too.

Optional: 140 Degree F Heat exchanger can be mounted on the Goliath vacuum system exhaust. Hotter water cleans better than cold water. If your supplied building water heating system is under 140 and you would like to boost your water temperature to 140 degrees F we can install a heat exchanger under the Goliath to absorb the heat from the vacuum motors. The nice thing about this heater is that it does not take any electricity to operate and heats the water with free energy. 140 degrees is the maximum in bound water temperature for this pumping system. Please check with your city regulations to see what water temperature you can have leave the sink and if you need this option.

Optional natural gas, diesel, propane, kerosene heating systems available if you want to clean with live steam and more pressure. Naturally these other system will require additional building requirements and employee safety issues that will require additional training. In the current format employees cannot get burned or have water pressure that will cut through the skin.

Question: What if we suck up a toothpick and it gets stuck in the middle of the hose and starts to collect trash and hair and creates some vacuum loss?

Answer: Just suck up some ice cubes and the ice will travel down the hose at over hundred miles per hour and will break the toothpick on impact and does not add to the clog.

Question: Can we use this system as a central vacuum system for everyday dry dirt pick up?

Answer: Yes, but because it is designed for wet pick up you have to choose to either use the optional dry dirt collection bags on the inside of the Goliath vacuum tank or add a dust downer. A dust downer is a spray jet that sprays water into the vacuum hose to turn the dry dirt into mud as it passes through the vacuum hose. With this dust downer system means you are consuming a small amount of water all the time. If you use the dry bag option, this bag must be removed before wet pick up.

Optional

Clean Storm Grout Master Cleaning Tool 300psi - 1200 psi 20190919 Wand

For the first time in history, pressure wash tile and grout with a standard 500 psi portable carpet cleaning machine.

No high pressure pump required.

Watch Video On Link!

>

.20130628djc

*Availability: This product was added to our catalog on Friday 28 June, 2013*