

>



Model Number: SV725-3002

Kohler 24hp Courage Vertical Twin Cylinder Engine SV725-3002 GTIN N/A

Manufacturer: Kohler

Kohler 24 hp Courage Vertical Twin Cylinder Engine PA-SV725-3002, Factory superceeded by p/n [KT735-3019]

Professional Grade Design.

Professional grade engineering for the consumer. Cool-running OHV design and tough cast-iron cylinder bore provides better fuel efficiency, more torque per unit of displacement and means your engine will last longer in harsh mowing conditions - so you can keep your mower longer and avoid costly trips to the repair shop.

Durable, Long Life Design.

The dual-seal, top- mount air filter keeps debris out of the engine and the internally vented carburetor provides added protection in dirty conditions. A modulated cooling fan reduces noise and optimizes air flow for a longer engine life.

High Power Performance.

Consistent-Cut technology delivers more consistent power to your mower deck in extreme load conditions, maximizing cutting, bagging, and mulching performance. So you can rest assured knowing there will be less clumping and missed areas.

Comfortable Operation.

Tough on grass, easy on you. V-Twin design provides smooth operation and the acoustically dampened air induction system reduces noise for quieter operation. This engine also features a flip-up air cleaner cover that allows for quick inspection and change

Reliable Starting.

High-torque inertia drive starter ensures quick, reliable starting in all conditions.

Increased Efficiency.

Overhead valve design makes KOHLER® engine more fuel efficient and provides more power per displacement while emitting fewer harmful exhaust gasses..

User-Friendly Maintenance.

High Power Performance.

>

Reliability and Long Life Design.

Quiet, Smooth Operation.

Easy Dependable Starts.

Engine Type:

4-cycle, gasoline, OHV, twin-cylinder, air-cooled, vertical shaft, full pressure lubrication with full-flow filter, aluminum head and crankcase with cast iron cylinder liners.

Model

Courage SV725

Max Power @3600 RPM hp (kW) 1
24 (17.9)

Displacement cu in (cc)
44 (725)

Bore in (mm)
3.3 (83)

Stroke in (mm)
2.6 (67)

>

Max Torque lbs. ft (Nm)¹
41.5 (56.2)

Compression Ratio
9:1

Dry Weight lbs (kg)
91 (41.3)

Oil Capacity U.S. quarts (L)
2 (1.9)

Lubrication
Full pressure w/full-flow filter

Dimensions L x W x H in
18.5 x 17.8 x 13.4

Backpressure Limit 2
50

J1995 Power hp (kW) 3
20.8 (15.5)

J1995 Torque lbs ft (Nm) 3
35.7 (48.4)

* Length is air cleaner cover to end of blower housing. Width is side of blower housing to opposite side of blower housing. Height is mounting surface to grass screen.

¹ Max Power (hp) and Max Torque (lbs ft) specifications for Kohler general purpose engines are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed according to SAE J1995 without the air cleaner and muffler. Actual engine power and torque are lower and affected by accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed, ambient operating conditions (temperature, humidity and altitude) and other factors. This J1940 / J1995 rating provides consistent measurement to customers who may want to control the intake and exhaust features of the engine. For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and

>

without incurring obligation.

2 Inches of H2O @ 3600 RPM WOT

3 J1995 power and torque certified by 3rd Party Witness

Kohler Videos

Owners Manual

Service Manual

<http://www.smallenginesuppliers.com/shop/agora.cgi>

\$849

-->

Standard Features:

- 1.125" Diameter x 4.36" PTO Length, 7/16-20 Crankshaft
- Cast-Iron Cylinder Liners
- 10" D.B.C., 4 Cored Holes (For OEM Self-Tap)
- Full Pressure Lubrication
- Oil Filter
- Automotive Style Dipstick (Yellow)
- 7/16" External Square Oil Drain Plug
- Stellite® Exhaust Valves
- 12V Bendix Electric Starter
- 15A Regulated Charging System
- Digital Advance Ignition System (DSAI) - SV735 only
- RFI/Ctick Compliance
- Modulated Cooling Fan
- Fixed Grass Screen Guard
- Carburetor w/Fuel Shutdown Solenoid
- Pulse Fuel Pump
- 51 Micron Fuel Filter
- Single Wire Controls - Throttle and Choke
- Mechanical Governor
- Torx Head Boden Screws
- Dual Element Air Cleaner
- Standard HP Decal (Black with Silver Lettering)
- Engine Plate with Emission Certification
- Governed Idle Speed 1750 (+150/-250) rpm
- High Speed 3300 (+/- 75) rpm
- Owner's Manual (English)
- Color-Black with Cast Aluminum

Standard Features Plus:

- EVAP

>

20130721dj

Availability: This product was added to our catalog on Sunday 21 July, 2013