

>



Model Number: SH265-0102

Kohler Courage 6.5hp Horizontal Shaft Engine SH265-0102 Lombardini (International)

Manufacturer: Kohler

Kohler Courage 6.5hp Horizontal Shaft Engine SH265-0102 Lombardini (For use in EU, Australia and New Zealand)

Gasoline Engine, 4 Cycle, 6.5 Hp, 3600 Engine Rpm, Gross Torque 6.5 Lbs Ft, Horizontal Shaft Orientation, Fuel Tank Capacity (qt.) 13.5, Overall Width (in.) 14.3, Overall Depth (in.)

6.5hp Kohler Courage Engine

Universal Replacement engine for Power Rakes, Truck Sprayers, Pressure Washers, Tillers, Brick Saws

Replacement engine for GX160

OHV, dual ball bearing PTO, cast iron cylinder liner, Recoil start
2 year consumer warranty, 90 day commercial warranty

Sales Brochure

Owners Manual

Service Manual

Standard Features:

- Overhead Valve Design
 - Electronic Ignition
 - Dual Element Air Cleaner (Unless otherwise mentioned)
 - Dual Oil Fill Locations
 - Dual Oil Drains
 - Cast Iron Cylinder Liner
 - 3.6 L Metal Fuel Tank with Strainer
 - Fuel Shut-off Valve (Unless otherwise mentioned)
 - Engine Mounted Throttle and Choke Controls, Remote Throttle Ready
 - Oil Sentry™ Switch Installed (No Light)
 - Dual Ball Bearings, PTO and Flywheel
 - Metal Blower Housing
 - Indexable Recoil Starter
 - PTO Face
 - For engines with SAE crankshaft: 3.625" (92.08 mm) Diameter (4 + 1 Holes) 5/16-24 UNF-2B Thread.
 - For engines with Metric crankshaft: 3.625" (92.08 mm) Diameter (4 + 1 Holes) M8x1.25-6H Thread.
 - Large Capacity Muffler w/Heat Shield
 - Multi-Lingual Owner's Manual
 - Color - Black with Cast Aluminum
 - Important Compliance Information:
- 1.Specs containing -3XXX are CARB Tier III, EPA Phase 3 and RFI compliant (Can

>

be sold globally)
2.Specs containing -0XXX are EU Stage 2 and RFI compliant (For sale in EU, Australia and New Zealand)
3.Specs containing -1XXX do not meet any compliance. These engine cannot be sold in US, Canada, EU, Australia and New Zealand (For sale in rest of the world)
Ship Weight 40 lbs

Standard Features Plus:

• Variable Speed,

• Crankshaft - 0.75" (19.05 mm) Diameter x 2.42" (61.47 mm) PTO Length, Tapped 5/16-24 UNF

• Recoil and electric start with key box and 10 amp charging

Availability: This product was added to our catalog on Sunday 04 August, 2013