


>



Model Number: KE28HA

General Pump KE28HA, 16.1gpm 2170psi Industrial

Manufacturer: General Pump

General Pump KE28HA 16.1 gpm 2170 psi Industrial

General Pumps - KE28HA has a Triplex Plunger Pump, available in 6 flows

• Patent-pending, symmetrical power end design featuring top and bottom mounting holes allowing for easy left to right shaft conversion
Low-high pressure packing desing with integrated cooling system.
High volumetric efficiency suction and delivery valves - featuring new spherical design of sealing areas
Splash Lubrication

1450 RPM

16.1 GPM / 61 Liters per min

2170 psi / 150 bar

Needs 24.5 Hp or 18 KW to turn it.

1" NPT inlets

1/2" NPT outlets

Righ Hand Shaft - Anti-clockwise turn

45 psi Max inlet pressure

140 degrees F Max Water Temperature

1.181" / 30 mm Shaft size

Bore/stroke : 1.102 in / 28 mm

Pump size 15.2" X 13.4" X 7.7"

Oil Capacity: 67.63 oz (2 Liters) - GP 220 Oil

Weight: 88 lbs/ 40 KG

Owners Manual

Other Models

. General Pump KE28HA 16.1gpm 2170psi Industrial

General pump Maintenance Guide

Sales tax collected in TX and CA

Availability: This product was added to our catalog on Tuesday 17 September, 2013