

>



Model Number: CH620-3009

Kohler 18hp Command Pro Horizontal Engine CH620-3009 Basic Recoil and Electric Starter With Controls PA-CH620-3107

Manufacturer: Kohler

(PLEASE NOTE, AS OF 06/17/2022, THIS ENGINE IS ON BACKORDER 90+ DAYS!
CALL US TO GET UPDATED STATUS)

Print Owners Manual:

Service Manual

Warranty Information

Overview

PA-CH620-3009

CH620 BASIC W PANEL

18 HP Kohler Command Twin OHV

Crankshaft: (24014381-S) 1"(25.4) x 3"(76)

Drilled & Tapped 3/8-24 UNF

.25"(6.36 mm) key way

12 Volt Electric Start: (2509811-S) Solenoid Shift Style

Recoil Starter: (1216503-S) with Retractable pull rope

Alternator: (5475509)

Regulator: (4140309-S)

Oil Sentry (not connected)

Key switch: (2509932-S) Engine Mounted Assy

Fuel Pump: (2455910-S) Valve Cover Kit

Cylinder Type: Cast Iron Sleeves

Cooling System: Air Cooled

Oil Sensor: (2509927-S)

Oil Filter: (1205001-S)

Throttle Controls: (2422508-S) Manual

Air Filter: (4708303-S) Standard

Engine Features:

Throttle Controls: Engine mounted controls. Key Switch. Throttle & Choke Controls

Engine Features:

Standard Features: SMART-CHOKE carburetor * Electronic ignition system

Solenoid shift starter * Cast iron cylinder liners * Hydraulic valve lifters * Dual-element air filter with foam pre-cleaner

>

Full-pressure lubrication * Spin-on. full-flow oil filter * Overhead valve (OHV) design

In-line fuel filter * Engineered material blower housing * Mechanical fuel pump

CARB & EPA emission-certified * Dual oil drains * Easy-access oil fill/dipstick * Two-year limited warranty

Engine Applications: Also Use: PA-62505

Kohler 18 HP Command V-Twin Horizontal Engine. This gasoline-driven, 4-cycle, 18 HP engine has reliable features including: OHV, cast iron V-Twin cylinder liners, and aluminum block construction.

Kohler Command V-Twin OHV Horizontal Engine with Electric Start & 18 HP, CH18-62521

Durable, Long Life Design.

Hydraulic valve lifters are oil pressurized, ensuring that push rods stay in constant contact with the rocker arms. Requiring no adjustment, the valve train is virtually maintenance-free. In addition, full-pressure lubrication delivers continuous lube to critical engine components, even at 25-degree angle of operation and optional oil cooler regulates the oil temperature extending oil-change intervals. Large capacity, in-line fuel filter provides extra protection against dirt particles that can clog fuel lines.

High Power Performance.

Overhead valve technology provides greater volumetric efficiency and a higher compression ratio. This produces more power, improved fuel economy and cooling and reduces oil consumption. In addition, there is virtually no carbon buildup, reducing overall maintenance costs. The variable speed, mechanical governor promises smooth performance, regardless of application or fluctuating demands for power.

Reliable Starting.

Kohler Command PRO[®] electronic ignition system generates a stronger spark at low cranking speed and Automatic Compression Release (ACR) allows compression to escape during cranking to reduce pull force.

User-Friendly Maintenance.

High Power Performance.

Reliability and Long Life Design.

>

Quiet, Smooth Operation.

Easy Dependable Starts.

Engine Type:
4-cycle, gasoline, OHV, cast iron cylinder liners, aluminum block

Model

Command PRO CH620

Max Power @3600 RPM hp (kW) 1
19 (14.2)

Displacement cu in (cc)
41.1 (674)

Bore in (mm)
3.1 (80)

Stroke in (mm)
2.6 (67)

Max Torque lbs. ft (Nm)1
35 (47.5)

Compression Ratio
8.5:1

>

Dry Weight lbs (kg)
90 (41)

Oil Capacity U.S. quarts (L)
2 (1.9)

Lubrication
Full pressure w/full-flow filter

Dimensions L x W x H in
14 x 17.7 x 19.0

Backpressure Limit 2
50

* Length is grass screen to PTO mounting face. Width is spark plug to spark plug.
Height is top of air cleaner to mounting feet.

1 Max Power (hp) and Max Torque (lbs ft) specifications for Kohler general purpose engines are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed according to SAE J1995 without the air cleaner and muffler. Actual engine power and torque are lower and affected by accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed, ambient operating conditions (temperature, humidity and altitude) and other factors. This J1940 / J1995 rating provides consistent measurement to customers who may want to control the intake and exhaust features of the engine. For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.

2 Inches of H2O @ 3600 RPM WOT
Features + Benefits

- Oil Sentry®;
- Includes muffler and manifold
- Engine controls
- Key switch
- Throttle
- Choke Controls

What's Included

>

- (1) Engine
 -
- Key Specs

Engine Displacement (cc)

624

Start Type

Electric

Engine Type

Command Pro V-Twin - CH18 - OHV

Rated Power (HP)

18

Torque (ft./lbs.)

32.8

Displacement (cu. in.)

38.1

Shaft Output

Horizontal

>

Shaft Diameter (in.)

1 1/8

Shaft Length (in.)

4

Shaft End Tapped (Diameter (in.)/Threads per inch)

7/16 - 20

Shaft Rotation (From PTO Shaft Side)

Counterclockwise

Cylinders (qty.)

2

Cylinder Bore

Cast iron

Bore x Stroke (in.)

3.03 x 2.64

Compression Ratio

8.5:1

Cooling System

>

Air cooled

Air Cleaner Type

Dual element air filter with foam pre-cleaner

Fuel Type

Gasoline

Fuel Pump

Mechanical

Fuel Filter

In line

Oil Capacity (qt.)

2

Lubrication System

Full pressure

Ignition System

Electronic

Governor System

Manual

>

Carburetor

Smart Choke

Max. RPM

3,600

Muffler Included

Yes

Bolt Circle (in.)

5 5/8, 7 3/4

Mounting Base L x W (in.)

7 1/4 x 3 1/2

Dimensions L x W x H (in.)

14 x 17 11/16 x 19

EPA/CARB Approval (California Air Resource Board)

Yes

Manufacturer Warranty

24 months parts / 24 months labor

>

Ship Weight

125.0 lbs

Item#

27666, CH620-3003, CH18S

Manufacturer Warranty: 24 months parts / 24 months labor
Note exact specifications and prices subject to change without notice.

Kohler CH20-3009 Basic with Both electric start and Pull rope start

Optional

..Steambrite 20 Hp Stainless TruckMount Carpet Cleaning Machine Kohler
Engine 36 Tuthill Blower Arimitsu Pump w/hoses and wand

Availability: This product was added to our catalog on Wednesday 18 December, 2013