

>



Model Number: 32605

KleenRite 32605 214HX Portable Extractor for Wet Dry Drapery Upholstery Cleaning Freight Included

Manufacturer: KleenRite

KleenRites 32605: Portable Extractor for Wet and Dry Cleaning Drapery - 214HX - KleenRite 2

## Description

The Rite one for the professional cleaner who wants to the advantage of instant, sustained heat when Wet or Dry cleaning Upholstery and Drapery plus Ceiling cleaning capability -- KleenRite's 32605 outstandingly represents the latest technology. Up to 3000 watts of heat are provided by our 11 pound heat exchanger.

Patented recirculating system provides you with the added advantage of constant hot solution being supplied continuously to the tool head. Easy flushing gives the operator the ability to change from Wet to Dry cleaning or to flush the solution system in minutes.

Meticulously engineered, the 214Hx gives you the benefits of solid state circuitry and the option of single or dual cord operation. The 214Hx is truly our finest light-weight portable.

Factory usually needs a full month for production.

## Features

Versatility: Wet or Dry Clean

Construction: Stainless Steel and Aluminum construction for durability. Solution carrying components compatible with upholstery, drapery, carpet and ceiling cleaning solvents and detergents.

Heat Exchanger: Internally mounted, Stainless Steel 3/8" diameter solution coil in an 11 lb. Aluminum heat storage cylinder for maximum instant heat transfer and sustained heat

Instant Heat: In line, dual range, thermostatically controlled heat settings: 3000 watts of heat offer instant 120 F dry cleaning solution, or a constant 208 F wet cleaning solution after an initial 4 minute warm-up.

Recirculating System: Continuously maintains heated solution at the cleaning head at all times and preheats cleaning solution in the solution tank with up to 3,000 watts of heat when not cleaning

Internal Solution Lines: Stainless Steel wire braid Teflon solution lines (aircraft quality) will withstand 3000 lb.. pressure, unchanged by temperatures over 450F

Simplified Flushing: The ability to change fluids or to easily flush the solution system

>

in minutes

Control Panel: Removable for easy accessibility to color-coded plug in wiring harness, high amperage rated switches for long life

Temperature Sensing System: Solid state circuitry, factory set at 1 F accuracy.

Electrical System: Solid state circuit board, available in 120 and 240V, 50/60 cycle with two 25' 12/3 non-marking power cords, single or dual operation

Heat Selection: Fail-safe low start-up at 120 F, dual activated switches for high range 208 F with thermostatically controlled back-up alarm and high limit automatic shut-off.

Serviceability: Lift-out control panel, removable side doors for easy service of remaining components. Also serviceable in operating mode. Wheels: 3 inch industrial type with ball bearing swivel  
Specifications

- Dimensions: 19" \* 13"W \* 23"H
- Weight: 47lbs. (actual)
- Vacuum: 1.48 HP, Two-stage blower, 92.5" water lift
- Pump: Centrifugal, 40 psi, viton seals, hydraulic fittings
- Heater: 3000 Watt inline heater
- Solution Tank: Stainless Steel, 3 gallon, 100 mesh Stainless Steel internal filter.
- Recovery Tank: Stainless Steel, 3.8 gallon, waster valve with viton seals.
- Lids: Impact resistant solution and vacuum lids
- Handle: Stainless Steel
- 2 Cord Unit

Manual  
Includes

- Vacuum Hose: L 1 1/4" \* 15'
- Exhaust Hose: 1 3/8" \* 25'
- Solution Hose: 1/4" \* 15' hose, brass disconnects
- Warranty: 2 years on components. Lifetime guarantee on Stainless Steel tanks and Aluminum base

>

## Options

KleenRite 20208REC Recirculating Carpet Cleaning Wand 12in x 1.5in Pipe 2  
(Dual 11003 Jets) 1200psi

KleenRite 20045 Recirulating Upholstery Tool wand

E20190613JMG

*Availability: This product was added to our catalog on Sunday 06 February, 2005*