


>



Model Number: 2087-593-135  
Shurflo 2087-593-135, 12volts 50psi 2.8 gpm  
Manufacturer: Shurflo

Model

2087-593-135

Description

3.0 GPM open flow, Viton® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports, Poly Housing

Voltage

12 VDC

PSI

10

20

30

40

50

>

BAR

0.7

1.4

2.1

2.8

3.4

GPM

2.8

2.69

2.36

1.05

1.42

L/min

10.6

>

10.2

8.9

7.8

5.4

Amps

5.3

5.5

6.7

7.7

8.0

Data Sheet  
International shipping?  
You can ship either one or two of these pumps for the same \$80 by the US Post  
Master to almost every country in the world.

Features:

- |                         |                                   |
|-------------------------|-----------------------------------|
| Self Priming up to 12   | vertical feet (3.7m)              |
| Chemical resistant      | materials                         |
| Can run dry without     | damage                            |
| Rocker switch protected | from the elements by a clear boot |

>

Additional features of pump with Electrical package

Built-in on/off switch included  
2 pin connector on power lead

These new models include an aesthetically pleasing molded assembly, housing a rocker-type switch with international on/off symbols. Wiring is neatly routed into the molded assembly through form fitted entries, and strain relieved inside the housing.

Model

Description

2087-593-135

Demand Pump W/Electrical Package  
3.0 GPM open flow, Viton® valves, Santoprene®  
diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports, Poly Housing

Availability: This product was added to our catalog on Thursday 13 November, 2008