

>



Model Number: HTF2421S

General Pump HTF2421s, Emperor Up to 12 gpm 3000psi, 8.723-968.0, Freight Included

Manufacturer: General Pump

General Pump HTF2421s Emperor Up to 12 gpm 3000psi
Multi-gun and Multi-jet cleaning applications

1450 rpm - 10 gpm 3000 psi
or
1750 rpm - 12 gpm 2500 psi

Maximum Volume
10.0/12.0 gpm

Max. Discharge Pressure
3000/2500 psi

Maximum Pump Speed
1450/1750 rpm

Maximum Inlet Pressure
125 psi

Maximum Inlet Vacuum
9 ft. water (7.9 in Hg)

Bore
.945 in / 24 mm

Stroke
.826 in / 21 mm

Crankcase Oil Capacity
40.6 oz

Maximum Fluid Temperature
185°F

>

Inlet Port Thread
3/4-14 BSP-F

Discharge Port Thread
3/8-19 BSP-F

Shaft Diameter
.945 in / 24 mm

Weight
41 lbs

Dimensions
13.4 x 9.8 x 7.5 in

- Features patent-pending high tech packings
- Solid ceramic plungers
- Patent-pending inlet/outlet valve cage
- Nickel-plated inlet/outlet valve plugs
- Nickel-plated forged brass manifold with exclusive lifetime warranty
- Designed for carpet cleaning and for use in industrial plant systems where hot water is required
- Available in L left-handed versions

Sales Brochure and Schematics

- General pump Maintenance Guide

Sales Tax Collected in TX and CA

Availability: This product was added to our catalog on Friday 06 June, 2014