

>



Model Number: Tt2028gbf  
General Pump Tt2028gbf, 8.702-673.0  
Manufacturer: General Pump  
General Pump, Tt2028gbf - 8.702-673.0

#### OEM Associations

102121

5-23022

726492

830009

87026730

Triplex Plunger Pump  
Direct Drive Gas Flange  
Maximum Volume: 2.85 GPM  
Maximum Discharge Pressure: 2000 PSI  
Maximum Inlet Pressure: 125 PSI  
Maximum Pump Speed: 3400 RPM  
Minimum Horsepower Requirements: 5.9 hp for gas engine  
Bore: .591" (15mm)  
Stroke: .260" (6.6mm)  
Crankcase Capacity: 11.2 oz. Nondetergent SAE 30W oil  
Maximum Fluid Temperature: 165 degrees F.  
Inlet Port Thread: 3/8" FPT

>

Discharge Port Thread: 1/4" FPT

Shaft Diameter: 3/4" Gas Flange

Dimensions: 7.0" x 7.2" x 5.5"

Weight: 9 lb.

Lubrication: Fill the crankcase to oil gauge window per specifications with Nondetergent SAE 30W oil. Change the oil after a 40 hour break-in period, then every three (3) months or 500 hour intervals thereafter

*Availability: This product was added to our catalog on Friday 06 June, 2014*