

>



Model Number: CW033GL-4/1

Hydro-Force Hardwood Preservation Satin Finish CW033GL-4/1 case

Manufacturer: HydroForce

Hydro-Force Hardwood Preservation Finish
Satin

Hardwood Preservation Finish (Gloss or Satin) is designed to be used as a preservation finish over an existing urethane finish over a hardwood floor. It is a low solid blend of urethane and acrylic so that it can be easily applied over a urethane finish after a thorough cleaning and a properly prepared base finish. The base finish can be prepared by the extraction or abrasive cleaning method. This preservation finish serves as the wear coat and protects the original finish of the floor. Apply the finish immediately after the extraction cleaning system is finished. A second coat of finish is optional for the extraction cleaning system. Apply the finish about an hour after the abrasion cleaning system is completed. The abrasion cleaning system leaves the hardwood floor damp making it necessary a dry time of about an hour. A second coat of finish is necessary for the abrasion cleaning system. To apply, use terry cloth covers and a finish applicator. Once a floor has dried naturally for approximately 45 minutes, a second coat of finish is then applied and also allowed to dry naturally. The end result is a clean, refinished and rejuvenated wood floor and a happy customer.

Dilution Ratios: RTU RTU pH: 7.8 Contains: 4/1 gallon Case

Sales tax collected on this product in the following states: AZ CA, CO, KS, MD, NE, NV, NC, TN, TX, UT, VA & WA

Availability: This product was added to our catalog on Tuesday 13 January, 2015