

>



Model Number: SBM860-ZF

DriStorm Goliath Flood Pumper Extractor 20gal 3 Stage Vac 85gpm Hoses Wand Link Hog
SBM860-ZF 120v

Manufacturer: Shazaam

85 gallon auto pump out!

Video of the Goliath Heated Electric Truckmount Package

Goliath

85 GPM 3 Stage Vac Flood pumper

The Industries Fastest Pumping Water Extraction Machine!

Tank Size: 20 gallon

Body Construction: Fiberglass box for durability,

Vacuum Motors: 3 Stage vacuum (Optional 8 stage system available)

Automation: 85 GPM sump pump with water level sensor (machines automatically
dumps the dirty water as you clean for non stop production) Draws 8 amps.

Features:

- Clear dome lid on slotted hinged,
- Single 50 ft. 12-3 power cords,

Extension Power Cord 50 ft 12-3 115 volt AX33 860831

- 12" rear wheels and swivel casters in the front.
- Front mounted GFI w/ waterproof cover.
- Built in Auto Defoamer with adjustment knob.
- 2" X 50 ft vacuum hose

AH30

>



>

Hose: Vacuum Hose - 50ft x 2.0in - Double Lined

- 1-1/2" Auto dump hose for floods
-

AH38C



Hose: Vacuum Hose - 50ft x 1.5in With Cuffs (Double lined)

- Machine will operate on one power cords
- Made in the USA
- Water Extraction Wand:
- Free

Mytee F200 Hose Mount Lint Hog Debris Carpet Cleaning Machine Hose
Filter for 2 inch vacuum hose

- Technical Specification:

>

- 2" vacuum intake..
- 1-1/2" cam lock adapter for flood restoration (seen in photo below)
- (2) Green lighted splash proof rocker switches.
- Blue tank/Grey base
- 100 C.F.M.'s
- 125" of Lift
- Gallon of liquid defoamer can be set on top of extractor on jobs where you need to cut some suds. (auto dump systems only dump water and not bubbles)

Single 3 Stage Vertical for longer bearing life is 50% stronger than 2 stage models

Unit Measurements:

- Handle height is 39". Machine dimensions" 41" H x 24" W x 30" L
- Weight (assembled) = 86 lbs. w/out cords.

Goliath Advantages:

1. 20 gallon recovery tank
2. Auto defoamer needle valve
3. 2" vac port will run either 2" or 1-1/2" vacuum hose
4. The highest pump out pump at 85 GPM
5. Stainless steel dump valve is another industry first. You will not be able to brake it or clog it or wear it out.
6. Switch plate cover will keep your water resistant switch covers in place. Unlike some other brands the clear water protection cover can fall off once the machine gets old or if it gets knocked around.
9. Now available with an optional 500 psi PumpTec pump, 8 stages of vacuum, heaters, more..

Owner's Manual

Color is not guaranteed. The current color is Blue.

Auto Defoamer with adjustment knob

Also available in 230-240 volts for \$350 extra + a one month lead time.

To see our vacuum motor testing visit

<http://www.steam-brite.com/forum/showthread.php?p=3004#post3004>

Starter packages available to clean:

>

Air Ducts, Tile and Grout Cleaning, Water Extraction, Carpet Cleaning (either high flow and high pressure),
Auto Detailing, Mattress, Upholstery, and Drape Cleaning.
Turn your Goliath into the worlds stronges shop vac with:

Shazaam: Dry Vacuum Option for Goliath Extractor
Date Added: Thursday 26 March, 2009
Manufacturer: Shazaam

shipping weight is 141#s including pallet; dimensions are: 48 X 40 X 48

OPTIONS:

Shazaam
Truckmount Kit

>



>

Shazaam: Convert Portable to a Truckmounted Carpet Cleaning Machine and
Leave outside with Generator, Reel, Power Cord

.20111021DJC

NOAH is a fully automated "Flood Control/Water Damage Machine" made with
the latest technology and your safety in mind.

With its automatic features; set monitoring system, 85 gallon per minute dumping
capacity and 117" of water lift of vacuum power, the NOAH can drain a full swimming
pool to the smallest spill on a floor.

NOAH is a portable machine with the highest quality, which is also very efficient and
easy to handle.

Model N-860Z

(capable of recovering water & debris)

Noah - 860Z is flood recovery and restoration / automatic dumping machine.

Designed to move liquid, sludge, and solids up to 3/8" diameter.

- Heavy duty fiber composite body
- Powerful one 3 stage vacuum motor
- 117" vacuum (in water lift)
- Air flow 99 (cfm)
- Flow rate 60 gpm (one gallon per second)
- 120 volt AC with 12 amperes (18 amperes max)
- 20 gallon recovery tank
- Easy access to all mechanical components
- Exterior dimensions H 32" x W 16" x L 21"
- Stationary handle
- 2-4-inch non marking casters
- 2-12-inch rear wheels
- Stainless steel lid
- 1-25-foot 12-3 electric power cord
- 14.5-inch double squeegee wand
- 50-foot vacuum and dump hose
- Shipping weight 100 Lb +

Brochure

Parts List

-->

Availability: This product was added to our catalog on Tuesday 13 July, 2010