

>



Model Number: 8005-733-155

Shurflo 8005-733-155, 60psi 115volt 1.4gpm With Pressure Switch, 1/2 In Male Pipe Connections, Freight Included

Manufacturer: Shurflo

Shurflo- Diaphragm Pump 3 Chamber, 1.4 GPM Open Flow, 115VAC Intermittant Duty, 60 PSI Demand Switch (adjustable 40-60 PSI), Viton Valves, Santoprene Diaphragm, Polypropylene Housing, 3/8" NPT Female Ports, UL/CSA Recognized, Typical Application: Soil Extraction, Carpet Cleaning

ShurFlo 115VAC 1.4 GPM Transfer Diaphragm Pump

ShurFlo 8005-733-155 Industrial Transfer Diaphragm Pump

115 Volt AC, 1.4 GPM open flow, 60 PSI Demand switch, Viton valves, Santoprene diaphragm. 3/8" NPT Poly (Female) Ports

- PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump
- CAM: 3.0 Degree
- CHECK VALVE: (2-Way Op.) Prevents Reverse Flow & 6 Ft. Head Forward Flow
- MOTOR: Permanent Magnet, P/N 11-150-00, Thermally Protected
- VOLTAGE: 115 VAC Nominal
- PRESSURE SWITCH: Adjustable Shut-Off (Range 40-60 PSI), Factory Set @ 60 PSI, Turn On 45 PSI +/- 5 PSI
- LIQUID TEMPERATURE: 170 Degrees Fahrenheit (77 Degrees Centigrade) Max.
- PRIME: Self-Priming Up To 8 Ft. Vertical,
- Max. Inlet Pressure 30 PSI (2.1 Bar)
- PORTS: 1/2" male Straight pipe
- MATERIAL OF CONSTRUCTION:
  - PLASTICS- Polypropylene
  - VALVES- Viton
  - DIAPHRAGM- Santoprene
  - FASTENERS- Zinc Plated Steel
- NET WEIGHT: 3.8 Lbs (1.72 Kg)
- DUTY CYCLE: Intermittent
- TYPICAL APPLICATIONS: Soil Extraction
- Used in baby changing stations.

International shipping?

You can ship either one or two of these pumps for the same \$100 by the US Postmaster to almost every country in the world.

- Model: 8005-733-155
- Shipping Weight: 4lbs
- Manufactured by: SHURflo

>

Zoro  
-->

Special order non stock pump  
Takes the factory 3 weeks to make.

*Availability: This product was added to our catalog on Wednesday 17 February, 2016*