

>



Model Number: HTXS1810S

General Pump HTXS1810S, Emperor Run, 2.7/3.1gpm 2000psi 1450/1750rpm, High Temperature

Manufacturer: General Pump

General Pump HTXS1810S

3.1gpm/ 1750 rpm or 2.7gpm/1450rpm

Emperor Run Dry

Handles super 185 degree F inbound hot water!

- Features patent-pending high tech packings
- Solid ceramic plungers
- Patent-pending inlet/outlet valve cage
- Nickel-plated inlet/outlet valve plugs
- Nickel-plated forged brass manifold with exclusive lifetime warranty
- Specifically designed to handle rigorous duty cycles, high temperatures and chemicals
- Ideal for use in carpet cleaning and other high pressure cleaning applications

SPECIFICATIONS - HTX1810S

Maximum Volume
3.1 gpm

Max. Discharge Pressure
2500 psi

Maximum Pump Speed
1750 rpm

Maximum Inlet Pressure
125 psi

Maximum Inlet Vacuum
3 ft. water (2.6 in Hg)

Bore
.709 in / 18 mm

Stroke

>

.512 in / 13 mm

Crankcase Oil Capacity
14.0 oz

Maximum Fluid Temperature
185°F

Inlet Port Thread
1/2-14 BSP-F

Discharge Port Thread
3/8-19 BSP-F

Shaft Diameter
.945 in / 24 mm

Weight
18 lbs

Dimensions
8.4 x 8.3 x 5.6 in

General pump Maintenance Guide
Sales Brochure

Used on the Sapphire Scientific 370SS Truckmount
Sales tax collected in TX and CA

Availability: This product was added to our catalog on Sunday 24 April, 2016