>



Model Number: 77027045031

Liquid Nails Silicone Premium Universal Sealant LS-205 77027045031 0022078400735 348039899

Manufacturer: PPG Paints

Liquid Nails Silicone Premium Universal Sealant is a high performance
Description
Clear 100% . Silicone Premium Universal Sealant (LS-205) is a high performance sealant for outstanding water resistance and flexibility. Won’t shrink or crack. Withstands harsh temperatures.
Features

- Permanently flexible
- Gives a mildew resistant seal
- Waterproof seal
- Ideal for high moisture areas
- Excellent durability
- Won't crack or shrink
- Great for kitchen & bath

Recommended For

Sealing

- Window and door frames
- Siding and trim
- Carpet cleaning machines and carpet wands
- Chair railings
- Sinks, bathtubs and showers
- Molding, baseboards, and siding
- Vanities
- Pipes and plumbing fixtures
- Tiles

Adheres

- Plaster (primed)
- Painted surfaces
- Concrete (primed)
- brick (primed)
- stone (primed)

Steambrite Supply

- Masonry (primed)
- Aluminum
- Vinyl
- Wood
- Stucco
- Glass
- Metal
- Fiberglass (primed)

Not Recommended For

Non-adhesive

- Unprimed concrete, brick, masonry, plaster & stone

- Use below the water-line
- Wet, green or oily lumber
- Aquariums
- Marble
- Fireplaces
- Automotive uses
- Stove pipes

Specifications

- 10.1 oz
- Indoor/Outdoor
- Base: Silicone rubber
- Type: Acetoxy cure
- Colors: Clear and White
- Appearance: Smooth
- Application Temperature: 10–100° F (-12–38° C)
- Service Temperature: -62–450° F (-52–232° C)
- Extrudability: Good
- Durability: 50 year
- Elongation: 400%
- Flexibility: Excellent
- Volume Shrinkage: Less than 5%
- Slump: Max 0.15”

Steambrite Supply

>

• Shore “A” Hardness: 25
• Total Joint Movement: 25%
• Water Resistance: Excellent
• Exterior Weathering: Excellent
• Aging: Excellent
• Freeze-Thaw Stable: Passes 5 cycles
• Bleed: None
• Staining: None
• Odor: Slightly acidic
• Tack Free Time:
• Tack at drying time - 15 minutes
• Tack at 24 hours - none
• Drying Time: Sets in 24
• Weight Per Gallon: 8.7 pounds (3.94 kg)
• Viscosity: 400,000 CPS
• Solids: 100%
• Flammability: Nonflammable
• Flash Point: 100– 110° F (38–43° C)
• Coverage: 30 lineal ft. (9.14 lineal meters) using 1/4" (.64cm) bead
• Shelf Life: One year from date of purchase
• VOC: <3% by wt. - White <50% by wt. - Clear
• MSDS
• Tech Data

Will not paint over. Keep from freezing during transport, so it might not be recommended to ship year around.
Compare to current or past OEM associations:
LS-205
77027045031
0022078400735
348039899

Availability: This product was added to our catalog on Thursday 17 November, 2016