

>



Model Number: 20170224

Clean Storm 20170224, Panel Mount Rotary Turbo Laser Nozzle, 500-4000 psi HOT Heavy Duty 2.5 gpm

Manufacturer: Clean Storm

A Plus+ Heavy Duty Panel Mountable Rotary Turbo Nozzle for HOT Water and 4000 psi

Panel Mountable means you can install in a cleaning box or parts washer machine. To mount, tap 7/8-14 thread count into your panel, Screw in the turbo nozzle and install a 3/4-16 backup thread nut to secure. Inbound water connection is 1/4" Fip. Use several nozzles in different locations in your box/ machine to provide the correct flow and impact pattern you desire. Perfect for parts and equipment cleaning boxes, conveyor belt cleaning, specialty tools, etc...

Works with all pressures between 500 psi to 4000 psi

Heavy Duty Construction with upgraded seals for hot water and higher pressures.

0 degree spray rotates at a 25 degree pattern.

Available in flow rates from 2.5 to 4 gallons per minute.

Works with both cold and hot pressure washers with water at 212 degrees.

Supplies the power of zero degrees but rotates at up to 5000 rpm.

Note gpm flow rates are calculated at 4000 psi as less pressure means less flow and more pressure is more flow.

Caution: Not for use on painted or softer surfaces (example car's exterior)

Please note turbo nozzles can harm you if you get near any body parts/ skin. Will also cut through wood and shoes!

This part number 2.5 gpm @ 4000 psi

Default color of plastic is heavy duty black but the color/shade is not guaranteed.

Tips:

1. Start turbo nozzles in the downward position and then raise lance to higher level.
2. Installation can direct onto a lance, with an optional male 1/4" QC Plug, or with an optional filter and plug combination. (see below) You can even pair more than one together with a "Y" or "T" brass fittings.

Please note the filter is highly recommended with use on HOT pressure washers as coil rust in the nozzle with jam up the rotary action.

Question: if my hot pressure washer is set to 240 degrees F, is it OK to use this nozzle?

>

Answer: Yes, The water cools down up to 30 degrees through most 100 ft hose runs an this is still OK to use. The nozzle is designed for water up to 4000 psi @ 212 degrees F at the tip.

Question: Can I use this 4000 psi for cold water and low pressure situations?

Answer: Yes

Optional:

BioForce Hydra 50 GB 1000 psi HOT Parts Washer FREE Shipping

Optional

Rotary Nozzle Inline Filter High Pressure 1/4in QD X 1/4"Mip Brass

8.709-979.0 Landa Legacy Hotsy Shark 342042

Installs directly into the back of the turbo nozzle and filters rust from water protecting your rotary nozzle.

Optional

QD Coupler 1/4" Mip X 1/4 Male Nipple Plug Stainless Steel 8.707-140.0 -

Landa Legacy Hotsy Shark

Installs directly into the back of the turbo nozzle for quick coupler action at the end of your lance

>

Legacy 1/4 Inch Female Socket Quick Coupler X 1/4" Fip Connection 4000
psi 98021640
Used to convert the end of your lance into quick coupler jet and nozzle change
out.

Availability: This product was added to our catalog on Friday 24 February, 2017