

>



Model Number: SC40V

Sirocco SC40V 40in Triple-Wide Vacuuming Surface Cleaner (Factory needs 2 - 4 week build time)

Manufacturer: Sirocco

Sirocco SC40V 40in Triple-Wide Vacuuming Surface Cleaner (Factory needs 2 - 4 week build time)

**\*\* THERE ARE NO RETURNS ON THIS ITEM! ALL SALES FINAL! \*\***

#### Description

Eliminate over-spray while pressure washing shopping centers, flat-work, warehouse floors, tile surfaces, etc. production style! Sanitize with up to 250°F at 20,000 to 40,000 sq ft. per hour, and have dry floors in minutes! Crazy fast work speed &ndash; great for compelling demonstrations!

The MOST important reason to own one of these is &ldquo;instant-capture&rdquo; for controlling over-spray, but when you see your &ldquo;quality of clean&rdquo; improve too, don&rsquo;t be surprised. The vacuum draws the water away from the spray area, removing the water-puddle, thus allowing better spray-impact and a faster-spinning spray-bar.

When the pressure washing and wash water control are done simultaneously, there&rsquo;s NO rinsing required &ndash; and the net increase in work-speed quickly pays for the equipment!

#### Features

- Triple-wide 40" vacuuming deck
- Powerful 2-armed spray bars for applications requiring up to 10 gpm, includes 25&deg; spray nozzles and hi-volume connect hose.
  - use 2-armed spray bars with higher temp (up to 250&deg;F) and reduced flow applications, as with interior cleaning where maximum capture is required.
- Uses 1/4" MPT nozzles
- Includes 3 DYC height-adjustable swivels
- Nozzle size available in #1.5
- Triple rear vacuum ports (for reclaiming in forward motion)
- Inner and outer skirts (for preventing over-spray)
- Dual inlets for multiple machine feed, each with high-pressure filters (to insure clean spray nozzles)
  - Dual high-pressure connect hoses
  - 1:3 Vacuum hose manifold with 3ea. vacuum connect hoses
  - 4ea. height adjustable 4" caster wheels
  - Includes partial mounting hardware with 2ea. 18" attaching arms
  - Use as trailing arms for mounting underneath mower. This surface cleaner was built to be or use as trailing arms when mounting underneath mower.
  - Use as extension arms when mounting in the front of the mower. This surface cleaner was built to be mounted under a mower, so if it's mounted to the front the driver must be extra cautious during operation, especially on uneven surfaces.

#### Specifications

- Max PSI: 5000

>

- Max GPM: 20+ (12 to 16 gpm is best for 98% capture)
- Max Temp: 250&deg;F
- Deck Diameter: 40"
- Requires 350-650 CFM

#### Notes

- Pictured with push bars, available for additional \$199
- This is for forward motion reclaim only, because of this it requires less CFM than a surface cleaner that reclaims in both forward and reverse directions. It's also lighter weight and more compact (fewer hoses, etc.).
  - Keep in mind, the larger the surface cleaner deck, the more it will dislike uneven surfaces! Plan accordingly! Surface cleaners work BEST on FLAT surfaces!
  - Lower flow and higher temperatures are MUCH easier to reclaim with, and is recommended for 98% instant capture.

[https://pressurewasher.net/products/40-vacuuming-surface-cleaner?\\_pos=2&\\_sid=142025680&\\_ss=r&variant=13466204897315](https://pressurewasher.net/products/40-vacuuming-surface-cleaner?_pos=2&_sid=142025680&_ss=r&variant=13466204897315)

-->

*Availability: This product was added to our catalog on Wednesday 29 November, 2017*