

>



Model Number: 20211021

Clean Storm 20211021 Heated Electric Pressure Washer 1500psi 3 Gpm 3Hp 5 Gal Tank 230 Volts 365 lbs

Manufacturer: Clean Storm

Clean Storm 20211021 Heated Electric Pressure Washer 1500psi 3 Gpm 3Hp 5 Gal Tank 230 Volts 365 lbs

Clean Storm Hot Water Pressure Washer is electric powered and uses diesel fuel to heat the water—this is often referred to as an oil fired burner system. All systems that use or burn a fuel should be operated outdoors or properly vented.

Features include an industrial motor that is totally enclosed and thermal overload protected, industrial triplex plunger pump with ceramic plungers and stainless steel valves is equipped with low pressure chemical injection and system is protected by unloader valve and secondary pressure pop off. Burner system includes a rust free fuel tank, schedule 80 coil with stainless steel wrap, is controlled by an adjustable thermostat and temperature limit switch for a maximum temperature 195° F. The frame is industrial coated & tubing equipped with a wand/hose rack and rolls on two 13" tires. Heavy duty trigger gun with a dual wand with side handle valve allows for user to switch from high pressure cleaning to detergent application and is equipped with quick change 0°, 15°, 25°, and 40° nozzles.

Be sure to check the electrical requirements of the pressure washer and the compatibility with your electrical supply. If you have any questions just contact us or consult your local licensed electrician.

All systems that use or burn a fuel should be operated outdoors or properly vented.

Brand: Clean Storm

Water Type: Hot

Powered By: Electric Motor

Mounting Type: Cart

Flow Rate in GPM / LPM: 3 / 11.4

Horsepower: 3

Product Dimensions: 34" x 27" x 47"

Voltage / Amperage / Phase: 230 Volt / 20 Amp Surge / 16 Amp Run / 1 Phase

Pump Thermal Protection: Mechanical

Max Pump Inlet Water Temp: 140° F

Hose Dimension: 50' x 3/8"

Power Cord: 35' with GFCI

Ship Weight: 355

Heated By: Diesel Fuel

Burner Fuel Tank Capacity: 5 Gallon

Burner Fuel Type: Diesel Fuel

Burner Stack Dimension: 8" Exhaust.

>

Operating Pressure in PSI / Bar: 1500 / 103.5

Factory Installed
NEMA 6-20P Plug 20 amp 240 volt

Factory Installed on hot water out connection
22mm Male Plug X 3/8in Mip Pressure Washer Coupler 331306PA
8.709-545.0 85.300.133

Factory Installed
1 Gpm
Hydrotek NorthStar 784621 Pressure Washer Reed Flow Switch UPC
682491035244 100975

Optional

Can operate and dual 120 volt circuits with this option;
Power Joiner Step Up Inverter Electric AC Converts Dual 20 amp 115 Volt
outlets to 240 Volt 3 wire 20 amp Use [Reverse6-20R] Level 2

>

Availability: This product was added to our catalog on Tuesday 19 October, 2021