

>



Model Number: 20211222

Clean Storm 20211222 Stationary LP Gas Fired Electric Powered 2.5gpm, 2700psi Hot Water Pressure Washer 230Volt 25Amp

Manufacturer: Clean Storm

Clean Storm 20211222 Stationary LP Gas Fired Electric Powered 2.5 gpm, 2700 psi Hot Water Pressure Washer 230 Volt 25 Amp

The Stationary Industrial Hot Water Pressure Washers heated by L.P. Gas are designed to be used in a stationary location and will be need to be connected to a "gas line. Designed for efficient operation using the latest in forced air burner technology. All systems that use or burn a fuel should be operated outdoors or properly vented. Industrial hot water pressure washer features include an industrial motor that is totally enclosed and thermal overload protected, industrial triplex plunger pump with ceramic plungers and stainless steel valves is protected by unloader valve and secondary pressure pop off. Equipped with low pressure chemical injection for application of concentrate liquid detergents and solutions. The low pressure injector operates best with the "hose included, for longer length hoses and pipeline systems the injector will have to be relocated within "of the trigger gun. Burner system includes a schedule 80 coil with stainless steel wrap, and is controlled by an adjustable thermostat and temperature limit switch for a maximum temperature 195° F. The skid frame is industrial coated steel tubing. Heavy duty trigger gun with a dual wand with side handle valve allows for user to switch from high pressure cleaning to detergent application and is equipped with quick change 0°, 15°, 25°, and 40° nozzles. These models require venting and proper make up air for safety and proper combustion, consult your local HVAC professional.

## 20211222 Product Specifications

Brand: Clean Storm  
 Water Type: Hot  
 Powered By: Electric Motor  
 Mounting Type: Stationary  
 Flow Rate in GPM / LPM: 2.5 / 9.5  
 Horsepower: 5  
 Product Dimensions: 47" x 29" x 46"  
 Voltage / Amperage / Phase: 230 Volt / 25 Amp / 1  
 Pump Thermal Protection: Mechanical  
 Max Pump Inlet Water Temp: 140° F  
 Hose Dimension: 50' x 3/8"  
 Power Cord: 35' with GFCI  
 Ship Weight: 450  
 Heated By: L.P. Gas  
 Burner Fuel Type: L.P. Gas  
 Burner Stack Dimension: 8"  
 Operating Pressure in PSI / Bar: 2700 / 186

>

Optional:

Allows you to operate pressure washer on dual 20 amp 120 volt phases  
Video on link  
Power Joiner Step Up Inverter Electric AC Converts Dual 20 amp 115 Volt  
outlets to 240 Volt 3 wire 20 amp Use [Reverse6-20R] Level 2  
Unloader will have to be turned down to 2000 psi to use this option.

*Availability: This product was added to our catalog on Wednesday 22 December, 2021*